Undecane, 3-methyl-

Other names: (dl) 3-methylundecane

2-Ethyl-decane

3-Methylundecane

InChl=1S/C12H26/c1-4-6-7-8-9-10-11-12(3)5-2/h12H,4-11H2,1-3H3

InchiKey: HTZWVZNRDDOFEI-UHFFFAOYSA-N

Formula: C12H26

SMILES: CCCCCCCC(C)CC

Mol. weight [g/mol]: 170.33 **CAS:** 1002-43-3

Physical Properties

Property code	Value	Unit	Source	
gf	47.72	kJ/mol	Joback Method	
hf	-296.29	kJ/mol	Joback Method	
hfus	23.31	kJ/mol	Joback Method	
hvap	41.92	kJ/mol	Joback Method	
log10ws	-4.60		Crippen Method	
logp	4.783		Crippen Method	
mcvol	179.940	ml/mol	McGowan Method	
pc	1792.42	kPa	Joback Method	
rinpol	1171.00		NIST Webbook	
rinpol	1168.00		NIST Webbook	
rinpol	1173.00	NIST Webbook		
rinpol	1173.00	NIST Webbook		
rinpol	1168.00	NIST Webbook		
rinpol	1169.60		NIST Webbook	
rinpol	1170.00		NIST Webbook	
rinpol	1171.00		NIST Webbook	
rinpol	1169.00		NIST Webbook	
rinpol	1172.00	NIST Webbook		
rinpol	1165.00	NIST Webbook		
rinpol	1169.00		NIST Webbook	
rinpol	1173.00		NIST Webbook	
rinpol	1173.00		NIST Webbook	
rinpol	1170.00		NIST Webbook	
rinpol	1173.00		NIST Webbook	
rinpol	1172.20		NIST Webbook	

rinpol	1172.00		NIST Webbook
rinpol	1171.00		NIST Webbook
rinpol	1169.00		NIST Webbook
rinpol	1170.00		NIST Webbook
rinpol	1165.00		NIST Webbook
rinpol	1172.00		NIST Webbook
rinpol	1170.00		NIST Webbook
rinpol	1170.00		NIST Webbook
rinpol	1173.00		NIST Webbook
rinpol	1170.00		NIST Webbook
rinpol	1169.00		NIST Webbook
rinpol	1171.00		NIST Webbook
rinpol	1170.00		NIST Webbook
tb	473.52	K	Joback Method
tc	637.74	K	Joback Method
tf	218.50 ± 2.00	K	NIST Webbook
tf	215.20 ± 5.00	K	NIST Webbook
VC	0.702	m3/kmol	Joback Method

Temperature Dependent Properties

Property code	Value	Unit	Temperature [K]	Source
cpg	406.90	J/mol×K	473.52	Joback Method
cpg	440.58	J/mol×K	528.26	Joback Method
cpg	456.45	J/mol×K	555.63	Joback Method
cpg	471.71	J/mol×K	583.00	Joback Method
cpg	486.36	J/mol×K	610.37	Joback Method
cpg	500.43	J/mol×K	637.74	Joback Method
cpg	424.06	J/mol×K	500.89	Joback Method
dvisc	0.0030132	Paxs	253.92	Joback Method
dvisc	0.0012770	Paxs	297.84	Joback Method
dvisc	0.0006749	Paxs	341.76	Joback Method
dvisc	0.0004124	Paxs	385.68	Joback Method
dvisc	0.0002787	Paxs	429.60	Joback Method
dvisc	0.0002026	Paxs	473.52	Joback Method
dvisc	0.0101808	Paxs	210.00	Joback Method
hvapt	48.80	kJ/mol	421.00	NIST Webbook

rhol	729.30	kg/m3	323.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	736.60	kg/m3	313.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	743.90	kg/m3	303.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	751.10	kg/m3	293.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	758.30	kg/m3	283.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	691.90	kg/m3	373.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels
rhol	699.40	kg/m3	363.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels

rhol	707.00	kg/m3	353.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	714.40	kg/m3	343.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	721.90	kg/m3	333.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	729.30	kg/m3	323.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	736.70	kg/m3	313.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	744.00	kg/m3	303.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	751.30	kg/m3	293.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	

283.15 rhol 758.60 kg/m3

Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels

Correlations

Information Value

Property code	pvap
Equation	ln(Pvp) = A + B/(T + C)
Coeff. A	1.41901e+01
Coeff. B	-3.75824e+03
Coeff. C	-9.13150e+01
Temperature range (K), min.	361.64
Temperature range (K), max.	514.60

Sources

McGowan Method: http://link.springer.com/article/10.1007/BF02311772

NIST Webbook: http://webbook.nist.gov/cgi/cbook.cgi?ID=C1002433&Units=SI

Pressure: Crippen Method:

http://pubs.acs.org/doi/abs/10.1021/ci990307l

Crippen Method: https://www.chemeo.com/doc/models/crippen_log10ws

Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, poheethy Alkanes, and Hydrotreated Renewable Fuels:

The Yaws Handbook of Vapor

https://www.doi.org/10.1021/je400274f https://en.wikipedia.org/wiki/Joback_method

https://www.sciencedirect.com/book/9780128029992/the-yaws-handbook-of-vapor-pressure

Legend

Ideal gas heat capacity cpg: dvisc: Dynamic viscosity

Standard Gibbs free energy of formation gf: hf: Enthalpy of formation at standard conditions hfus: Enthalpy of fusion at standard conditions

hvap: Enthalpy of vaporization at standard conditionshvapt: Enthalpy of vaporization at a given temperature

log10ws: Log10 of Water solubility in mol/llogp: Octanol/Water partition coefficientmcvol: McGowan's characteristic volume

pc: Critical Pressurepvap: Vapor pressurerhol: Liquid Density

rinpol: Non-polar retention indices

tb: Normal Boiling Point Temperature

tc: Critical Temperature

tf: Normal melting (fusion) point

vc: Critical Volume

Latest version available from:

https://www.chemeo.com/cid/16-793-4/Undecane-3-methyl.pdf

Generated by Cheméo on 2024-05-04 05:39:48.641469083 +0000 UTC m=+17090437.562046398.

Cheméo (https://www.chemeo.com) is the biggest free database of chemical and physical data for the process industry.