

Heptane, 3-ethyl-4-methyl-

| | |
|-----------------------------|--|
| Other names: | 3-Ethyl-4-methylheptane 4-Methyl-3-ethylheptane |
| Inchi: | InChI=1S/C10H22/c1-5-8-9(4)10(6-2)7-3/h9-10H,5-8H2,1-4H3 |
| InchiKey: | JZBKRUIGSVOOIC-UHFFFAOYSA-N |
| Formula: | C10H22 |
| SMILES: | CCCC(C)C(CC)CC |
| Mol. weight [g/mol]: | 142.28 |
| CAS: | 52896-91-0 |

Physical Properties

| Property code | Value | Unit | Source |
|---------------|---------|----------------------|----------------|
| gf | 28.44 | kJ/mol | Joback Method |
| hf | -260.29 | kJ/mol | Joback Method |
| hfus | 14.61 | kJ/mol | Joback Method |
| hvap | 48.10 | kJ/mol | NIST Webbook |
| log10ws | -3.52 | | Crippen Method |
| logp | 3.859 | | Crippen Method |
| mcvol | 151.760 | ml/mol | McGowan Method |
| pc | 2139.38 | kPa | Joback Method |
| rinpol | 940.00 | | NIST Webbook |
| rinpol | 940.00 | | NIST Webbook |
| rinpol | 940.00 | | NIST Webbook |
| rinpol | 940.00 | | NIST Webbook |
| rinpol | 940.50 | | NIST Webbook |
| rinpol | 938.00 | | NIST Webbook |
| rinpol | 940.00 | | NIST Webbook |
| tb | 427.32 | K | Joback Method |
| tc | 596.92 | K | Joback Method |
| tf | 172.46 | K | Joback Method |
| vc | 0.584 | m ³ /kmol | Joback Method |

Temperature Dependent Properties

| Property code | Value | Unit | Temperature [K] | Source |
|---------------|-------|------|-----------------|--------|
|---------------|-------|------|-----------------|--------|

| | | | | |
|-------|-----------|---------|--------|---------------|
| cpg | 315.26 | J/molxK | 427.32 | Joback Method |
| cpg | 331.18 | J/molxK | 455.59 | Joback Method |
| cpg | 346.50 | J/molxK | 483.85 | Joback Method |
| cpg | 361.21 | J/molxK | 512.12 | Joback Method |
| cpg | 375.35 | J/molxK | 540.39 | Joback Method |
| cpg | 388.93 | J/molxK | 568.65 | Joback Method |
| cpg | 401.95 | J/molxK | 596.92 | Joback Method |
| dvisc | 0.0214146 | Paxs | 172.46 | Joback Method |
| dvisc | 0.0046771 | Paxs | 214.94 | Joback Method |
| dvisc | 0.0016877 | Paxs | 257.41 | Joback Method |
| dvisc | 0.0008129 | Paxs | 299.89 | Joback Method |
| dvisc | 0.0004693 | Paxs | 342.37 | Joback Method |
| dvisc | 0.0003059 | Paxs | 384.84 | Joback Method |
| dvisc | 0.0002171 | Paxs | 427.32 | Joback Method |

Correlations

| Information | Value |
|-----------------------------|-------------------------------|
| Property code | pvap |
| Equation | $\ln(P_{vp}) = A + B/(T + C)$ |
| Coeff. A | 1.42973e+01 |
| Coeff. B | -3.66022e+03 |
| Coeff. C | -5.79990e+01 |
| Temperature range (K), min. | 319.26 |
| Temperature range (K), max. | 465.33 |

Sources

| | |
|---|---|
| Crippen Method: | http://pubs.acs.org/doi/abs/10.1021/ci9903071 |
| Crippen Method: | https://www.chemeo.com/doc/models/crippen_log10ws |
| Joback Method: | https://en.wikipedia.org/wiki/Joback_method |
| McGowan Method: | http://link.springer.com/article/10.1007/BF02311772 |
| NIST Webbook: | http://webbook.nist.gov/cgi/cbook.cgi?ID=C52896910&Units=SI |
| The Yaws Handbook of Vapor Pressure: | https://www.sciencedirect.com/book/9780128029992/the-yaws-handbook-of-vapor-pressure |

Legend

| | |
|------------------|---|
| cpg: | Ideal gas heat capacity |
| dvisc: | Dynamic viscosity |
| gf: | Standard Gibbs free energy of formation |
| hf: | Enthalpy of formation at standard conditions |
| hfus: | Enthalpy of fusion at standard conditions |
| h vap: | Enthalpy of vaporization at standard conditions |
| log10ws: | Log10 of Water solubility in mol/l |
| logp: | Octanol/Water partition coefficient |
| mcvol: | McGowan's characteristic volume |
| pc: | Critical Pressure |
| pvap: | Vapor pressure |
| rinpolar: | Non-polar retention indices |
| tb: | Normal Boiling Point Temperature |
| tc: | Critical Temperature |
| tf: | Normal melting (fusion) point |
| vc: | Critical Volume |

Latest version available from:

<https://www.cheméo.com/cid/30-909-9/Heptane-3-ethyl-4-methyl.pdf>

Generated by Cheméo on 2023-12-01 13:10:25.532583516 +0000 UTC m=+3725474.453160832.

Cheméo (<https://www.cheméo.com>) is the biggest free database of chemical and physical data for the process industry.