

Disiloxane, 1,3-diethenyl-1,1,3,3-tetramethyl-

Other names:	1,1'-Divinyltetramethyldisiloxane 1,1,3,3-Tetramethyl-1,3-divinylsiloxane 1,1,3,3-tetramethyl-1,3-divinyldisiloxane 1,3-Diethenyl-1,1,3,3-tetramethyl disiloxane 1,3-Divinyltetramethyldisiloxane 1,3-diethenyl-1,1,3,3-tetramethyldisiloxane 1,3-divinyl-1,1,3,3-tetramethyldisiloxane 846574-60-5 Bisvinyltetramethyldisiloxane CD6210 Disiloxane, 1,1,3,3-tetramethyl-1,3-divinyl- Divinyltetramethyldisiloxane Tetramethyl-1,3-divinyldisiloxane Tetramethyldivinylsiloxane bis(ethenyldimethylsilyl) ether sym-Tetramethyldi(ethenyl)disiloxane
Inchi:	InChI=1S/C8H18OSi2/c1-7-10(3,4)9-11(5,6)8-2/h7-8H,1-2H2,3-6H3
InchiKey:	BITPLIXHRASDQB-UHFFFAOYSA-N
Formula:	C8H18OSi2
SMILES:	C=C[Si](C)(C)O[Si](C)(C)C=C
Mol. weight [g/mol]:	186.40
CAS:	2627-95-4

Physical Properties

Property code	Value	Unit	Source
log10ws	1.76		Crippen Method
logp	2.864		Crippen Method
rinpol	848.00		NIST Webbook
tb	412.00	K	NIST Webbook

Temperature Dependent Properties

Property code	Value	Unit	Temperature [K]	Source
---------------	-------	------	-----------------	--------

rhol	822.67	kg/m3	283.15	The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3-Diethenyl-1,1,3,3-tetramethyldisiloxane with aromatic hydrocarbons
rhol	817.77	kg/m3	288.15	The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3-Diethenyl-1,1,3,3-tetramethyldisiloxane with aromatic hydrocarbons
rhol	812.92	kg/m3	293.15	The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3-Diethenyl-1,1,3,3-tetramethyldisiloxane with aromatic hydrocarbons
rhol	808.00	kg/m3	298.15	The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3-Diethenyl-1,1,3,3-tetramethyldisiloxane with aromatic hydrocarbons
rhol	803.07	kg/m3	303.15	The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3-Diethenyl-1,1,3,3-tetramethyldisiloxane with aromatic hydrocarbons
rhol	797.99	kg/m3	308.15	Volumetric and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K

rhol	793.04	kg/m3	313.15	Volumetric and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K
rhol	788.05	kg/m3	318.15	Volumetric and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K
rhol	783.06	kg/m3	323.15	Volumetric and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K
rhol	778.04	kg/m3	328.15	Volumetric and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K

Sources

- The density, refractive index, and thermodynamic behaviour of binary mixtures of 1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds at T = (308.15 to 328.15) K: <https://www.doi.org/10.1016/j.jct.2013.12.025>
- Molar mass and refractive properties of the mixtures of 1,1,3,3-tetramethyl-1,3-diphenyldisiloxane with various organosilicon compounds: <https://www.doi.org/10.1021/acs.jced.5b00820>
- NIST Webbook of Fluid Properties: <http://webbook.nist.gov/cgi/cbook.cgi?ID=C2627954&Units=SI>
- Crippen Method: <http://pubs.acs.org/doi/abs/10.1021/ci9903071>
- Crippen Method: https://www.chemeo.com/doc/models/crippen_log10ws

Legend

log10ws:	Log10 of Water solubility in mol/l
logp:	Octanol/Water partition coefficient
rhol:	Liquid Density
rinpol:	Non-polar retention indices
tb:	Normal Boiling Point Temperature

Latest version available from:

<https://www.chemeo.com/cid/38-776-9/Disiloxane-1-3-diethenyl-1-1-3-3-tetramethyl.pdf>

Generated by Cheméo on 2024-04-20 07:45:35.554105156 +0000 UTC m=+15888384.474682466.

Cheméo (<https://www.chemeo.com>) is the biggest free database of chemical and physical data for the process industry.