

# p-methoxybenzylidene-hexyl-amine

<b>Inchi:</b>	InChI=1S/C14H21NO/c1-3-4-5-6-11-15-12-13-7-9-14(16-2)10-8-13/h7-10,12H,3-6,11H2,
<b>InchiKey:</b>	JKQZHTHLOZMZQU-NTCAYCPXSA-N
<b>Formula:</b>	C14H21NO
<b>SMILES:</b>	CCCCCN=Cc1ccc(OC)cc1
<b>Mol. weight [g/mol]:</b>	219.32

## Physical Properties

Property code	Value	Unit	Source
hf	-157.23	kJ/mol	Joback Method
hvap	55.42	kJ/mol	Joback Method
log10ws	-3.75		Crippen Method
logp	3.694		Crippen Method
mcvol	195.910	ml/mol	McGowan Method
pc	1783.35	kPa	Joback Method
rinpol	1843.00		NIST Webbook
rinpol	1843.00		NIST Webbook
tb	650.48	K	Joback Method
tc	858.54	K	Joback Method

## Sources

<b>McGowan Method:</b>	<a href="http://link.springer.com/article/10.1007/BF02311772">http://link.springer.com/article/10.1007/BF02311772</a>
<b>NIST Webbook:</b>	<a href="http://webbook.nist.gov/cgi/cbook.cgi?ID=R160133&amp;Units=SI">http://webbook.nist.gov/cgi/cbook.cgi?ID=R160133&amp;Units=SI</a>
<b>Crippen Method:</b>	<a href="http://pubs.acs.org/doi/abs/10.1021/ci990307I">http://pubs.acs.org/doi/abs/10.1021/ci990307I</a>
<b>Crippen Method:</b>	<a href="https://www.chemeo.com/doc/models/crippen_log10ws">https://www.chemeo.com/doc/models/crippen_log10ws</a>
<b>Joback Method:</b>	<a href="https://en.wikipedia.org/wiki/Joback_method">https://en.wikipedia.org/wiki/Joback_method</a>

## Legend

<b>hf:</b>	Enthalpy of formation at standard conditions
<b>hvap:</b>	Enthalpy of vaporization at standard conditions

<b>log10ws:</b>	Log10 of Water solubility in mol/l
<b>logp:</b>	Octanol/Water partition coefficient
<b>mcvol:</b>	McGowan's characteristic volume
<b>pc:</b>	Critical Pressure
<b>rinpol:</b>	Non-polar retention indices
<b>tb:</b>	Normal Boiling Point Temperature
<b>tc:</b>	Critical Temperature

Latest version available from:

<https://www.cheméo.com/cid/42-105-8/p-methoxybenzylidene-hexyl-amine.pdf>

Generated by Cheméo on 2024-04-26 07:25:43.191975439 +0000 UTC m=+16405592.112552761.

Cheméo (<https://www.cheméo.com>) is the biggest free database of chemical and physical data for the process industry.