

N-Acetyl derivative of o-bromoaniline

Other names:	Acetanilide, 2'-bromo- 2'-Bromoacetanilide 2-Bromo-N-acetylaniline o-Bromoacetanilide
Inchi:	InChI=1S/C8H8BrNO/c1-6(11)10-8-5-3-2-4-7(8)9/h2-5H,1H3,(H,10,11)
InchiKey:	VOBKUOHHOWQHfZ-UHfFFFAOYSA-N
Formula:	C8H8BrNO
SMILES:	CC(=O)Nc1ccccc1Br
Mol. weight [g/mol]:	214.06

Physical Properties

Property code	Value	Unit	Source
hf	-109.70	kJ/mol	Cheméo Relay (1.0)
hfus	22.11	kJ/mol	Joback Method
ie	8.50	eV	NIST Webbook
ie	8.17 ± 0.03	eV	NIST Webbook
log10ws	-2.24		Cheméo Relay (1.0)
logp	2.408		Crippen Method
mcvol	128.870	ml/mol	McGowan Method
tb	555.60	K	Cheméo Relay (1.0)
tf	332.53	K	Cheméo Relay (1.0)

Temperature Dependent Properties

Property code	Value	Unit	Temperature [K]	Source
cpg	267.43	J/mol×K	584.30	Joback Method
cpg	278.04	J/mol×K	624.00	Joback Method
cpg	287.86	J/mol×K	663.70	Joback Method
cpg	296.93	J/mol×K	703.40	Joback Method
cpg	305.29	J/mol×K	743.10	Joback Method
cpg	312.99	J/mol×K	782.80	Joback Method
cpg	320.08	J/mol×K	822.49	Joback Method

Sources

Joback Method:	https://en.wikipedia.org/wiki/Joback_method
McGowan Method:	http://link.springer.com/article/10.1007/BF02311772
Crippen Method:	http://pubs.acs.org/doi/abs/10.1021/ci990307l
Crippen Method:	https://www.chemeo.com/doc/models/crippen_log10ws
Cheméo Relay (1.0):	
Cheméo Relay (1.0, beta):	
NIST Webbook:	http://webbook.nist.gov/cgi/cbook.cgi?ID=C614766&Units=SI

Legend

cpg:	Ideal gas heat capacity
hf:	Enthalpy of formation at standard conditions
hfus:	Enthalpy of fusion at standard conditions
ie:	Ionization energy
log10ws:	Log10 of Water solubility in mol/l
logp:	Octanol/Water partition coefficient
mcvol:	McGowan's characteristic volume
tb:	Normal Boiling Point Temperature
tf:	Normal melting (fusion) point

Latest version available from:

<https://www.chemeo.com/cid/46-902-9/N-Acetyl-derivative-of-o-bromoaniline.pdf>

Generated by Cheméo on 2026-07-21 15:41:49.011427769 +0000 UTC m=+159604.853313144.

Cheméo (<https://www.chemeo.com>) is the biggest free database of chemical and physical data for the process industry.