Hexadecane, 7-methyl-

Other names: 7-methylhexadecane

InChl=1S/C17H36/c1-4-6-8-10-11-12-14-16-17(3)15-13-9-7-5-2/h17H,4-16H2,1-3H3

InchiKey: HZRSSYSIMDTFLT-UHFFFAOYSA-N

Formula: C17H36

SMILES: CCCCCCCC(C)CCCCC

Mol. weight [g/mol]: 240.47 CAS: 26730-20-1

Physical Properties

Property code	Value	Unit	Source
gf	89.82	kJ/mol	Joback Method
hf	-399.49	kJ/mol	Joback Method
hfus	36.26	kJ/mol	Joback Method
hvap	53.05	kJ/mol	Joback Method
log10ws	-6.70		Crippen Method
logp	6.734		Crippen Method
mcvol	250.390	ml/mol	McGowan Method
pc	1238.09	kPa	Joback Method
rinpol	1646.00		NIST Webbook
rinpol	1641.00		NIST Webbook
rinpol	1646.00		NIST Webbook
rinpol	1647.60		NIST Webbook
tb	587.92	K	Joback Method
tc	748.86	K	Joback Method
tf	266.35	K	Joback Method
VC	0.982	m3/kmol	Joback Method

Temperature Dependent Properties

Property code	Value	Unit	Temperature [K]	Source
cpg	667.18	J/mol×K	587.92	Joback Method
cpg	687.14	J/mol×K	614.74	Joback Method
cpg	706.30	J/mol×K	641.57	Joback Method
cpg	724.69	J/mol×K	668.39	Joback Method

cpg	742.33	J/mol×K	695.21	Joback Method	
cpg	759.24	J/mol×K	722.04	Joback Method	
cpg	775.45	J/mol×K	748.86	Joback Method	
dvisc	0.0070198	Paxs	266.35	Joback Method	
dvisc	0.0020606	Paxs	319.94	Joback Method	
dvisc	0.0008598	Paxs	373.54	Joback Method	
dvisc	0.0004468	Paxs	427.13	Joback Method	
dvisc	0.0002686	Paxs	480.73	Joback Method	
dvisc	0.0001789	Paxs	534.33	Joback Method	
dvisc	0.0001283	Paxs	587.92	Joback Method	
rhol	787.60	kg/m3	283.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	780.70	kg/m3	293.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	773.80	kg/m3	303.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	766.90	kg/m3	313.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	760.00	kg/m3	323.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	

rhol	753.10	kg/m3	333.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	746.20	kg/m3	343.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	739.30	kg/m3	353.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	732.40	kg/m3	363.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	725.40	kg/m3	373.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	787.60	kg/m3	283.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	780.70	kg/m3	293.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	

rhol	773.90	kg/m3	303.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	767.00	kg/m3	313.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	
rhol	760.20	kg/m3	323.15	Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dimethyl Alkanes, and Hydrotreated Renewable Fuels	

Sources

McGowan Method: http://link.springer.com/article/10.1007/BF02311772

NIST Webbook: http://webbook.nist.gov/cgi/cbook.cgi?ID=C26730201&Units=SI

Crippen Method: http://pubs.acs.org/doi/abs/10.1021/ci990307l

Crippen Method: https://www.chemeo.com/doc/models/crippen_log10ws

Density, Viscosity, Speed of Sound, and Bulk Modulus of Methyl Alkanes, Dohatky Mathades, and Hydrotreated

https://www.doi.org/10.1021/je400274f

https://en.wikipedia.org/wiki/Joback_method

Legend

Renewable Fuels:

Ideal gas heat capacity cpg: dvisc: Dynamic viscosity

gf: Standard Gibbs free energy of formation hf: Enthalpy of formation at standard conditions hfus: Enthalpy of fusion at standard conditions

hvap: Enthalpy of vaporization at standard conditions

Log10 of Water solubility in mol/l log10ws: Octanol/Water partition coefficient logp:

mcvol: McGowan's characteristic volume

pc: Critical Pressurerhol: Liquid Density

rinpol: Non-polar retention indices

tb: Normal Boiling Point Temperature

tc: Critical Temperature

tf: Normal melting (fusion) point

vc: Critical Volume

Latest version available from:

https://www.chemeo.com/cid/74-504-0/Hexadecane-7-methyl.pdf

Generated by Cheméo on 2025-12-06 05:30:02.692643559 +0000 UTC m=+4747200.222684224.

Cheméo (https://www.chemeo.com) is the biggest free database of chemical and physical data for the process industry.