

DISILOXANE, 1,3-DIMETHYL-1,1,3,3-TETRAPHENYL-

Other names: 1,3-dimethyl-1,1,3,3-tetraphenyldisiloxane
Inchi: InChI=1S/C26H26OSi2/c1-28(23-15-7-3-8-16-23,24-17-9-4-10-18-24)27-29(2,25-19-11-5-26)28-29
InchiKey: RFGGTTTPASBFBTB-UHFFFAOYSA-N
Formula: C26H26OSi2
SMILES: C[Si](O[Si](C)(c1ccccc1)c1ccccc1)(c1ccccc1)c1ccccc1
Mol. weight [g/mol]: 410.66

Physical Properties

Property code	Value	Unit	Source
hvap	115.01	kJ/mol	Cheméo Relay (1.0)
ie	8.29	eV	Cheméo Relay (1.0)
logp	3.782		Crippen Method
ss	570.20	J/mol×K	NIST Webbook
tb	658.98	K	Cheméo Relay (1.0)
tf	322.85	K	Solubilities of 1,3-dimethyl-1,1,3,3-tetraphenyldisiloxane in different solvents from (288.15 to 313.15) K

Temperature Dependent Properties

Property code	Value	Unit	Temperature [K]	Source
cps	503.20	J/mol×K	298.15	NIST Webbook
hfust	26.58	kJ/mol	321.95	NIST Webbook
hfust	26.58	kJ/mol	322.00	NIST Webbook
hvapt	93.30	kJ/mol	567.00	NIST Webbook
hvapt	64.40	kJ/mol	601.50	NIST Webbook

Sources

Crippen Method: https://www.chemeo.com/doc/models/crippen_log10ws
Cheméo Relay (1.0):

Cheméo Relay (1.0, beta):

Solubilities of
1,3-dimethyl-1,1,3,3-tetraphenyldisiloxane
in different solvents from (288.15 to
313.15) K;
Crippen Method:

<https://www.doi.org/10.1016/j.tca.2012.04.033>

<http://webbook.nist.gov/cgi/cbook.cgi?ID=C807283&Units=SI>

<http://pubs.acs.org/doi/abs/10.1021/ci990307l>

Legend

cps:	Solid phase heat capacity
hfust:	Enthalpy of fusion at a given temperature
hvap:	Enthalpy of vaporization at standard conditions
hvapt:	Enthalpy of vaporization at a given temperature
ie:	Ionization energy
logp:	Octanol/Water partition coefficient
ss:	Solid phase molar entropy at standard conditions
tb:	Normal Boiling Point Temperature
tf:	Normal melting (fusion) point

Latest version available from:

<https://www.chemeo.com/cid/86-351-7/DISILOXANE-1-3-DIMETHYL-1-1-3-3-TETRAPHENYL.pdf>

Generated by Cheméo on 2026-07-22 03:58:36.425604339 +0000 UTC m=+203812.267489765.

Cheméo (<https://www.chemeo.com>) is the biggest free database of chemical and physical data for the process industry.