

# Benzamide, 3,4-dimethoxy-N-propyl-

<b>Inchi:</b>	InChI=1S/C12H17NO3/c1-4-7-13-12(14)9-5-6-10(15-2)11(8-9)16-3/h5-6,8H,4,7H2,1-3H3
<b>InchiKey:</b>	IXLDZEGNMDSKHS-UHFFFAOYSA-N
<b>Formula:</b>	C12H17NO3
<b>SMILES:</b>	CCCN=C(O)c1ccc(OC)c(OC)c1
<b>Mol. weight [g/mol]:</b>	223.27

## Physical Properties

Property code	Value	Unit	Source
hf	-421.66	kJ/mol	Joback Method
hvap	70.80	kJ/mol	Joback Method
log10ws	-2.44		Crippen Method
logp	2.418		Crippen Method
mcvol	179.470	ml/mol	McGowan Method
pc	2244.00	kPa	Joback Method
rinpol	2046.00		NIST Webbook
rinpol	2046.00		NIST Webbook
tb	724.18	K	Joback Method
tc	927.60	K	Joback Method

## Sources

<b>Joback Method:</b>	<a href="https://en.wikipedia.org/wiki/Joback_method">https://en.wikipedia.org/wiki/Joback_method</a>
<b>McGowan Method:</b>	<a href="http://link.springer.com/article/10.1007/BF02311772">http://link.springer.com/article/10.1007/BF02311772</a>
<b>NIST Webbook:</b>	<a href="http://webbook.nist.gov/cgi/cbook.cgi?ID=U408000&amp;Units=SI">http://webbook.nist.gov/cgi/cbook.cgi?ID=U408000&amp;Units=SI</a>
<b>Crippen Method:</b>	<a href="http://pubs.acs.org/doi/abs/10.1021/ci9903071">http://pubs.acs.org/doi/abs/10.1021/ci9903071</a>
<b>Crippen Method:</b>	<a href="https://www.chemeo.com/doc/models/crippen_log10ws">https://www.chemeo.com/doc/models/crippen_log10ws</a>

## Legend

<b>hf:</b>	Enthalpy of formation at standard conditions
<b>hvap:</b>	Enthalpy of vaporization at standard conditions

<b>log10ws:</b>	Log10 of Water solubility in mol/l
<b>logp:</b>	Octanol/Water partition coefficient
<b>mcvol:</b>	McGowan's characteristic volume
<b>pc:</b>	Critical Pressure
<b>rinpola:</b>	Non-polar retention indices
<b>tb:</b>	Normal Boiling Point Temperature
<b>tc:</b>	Critical Temperature

Latest version available from:

<https://www.cheméo.com/cid/94-105-1/Benzamide-3-4-dimethoxy-N-propyl.pdf>

Generated by Cheméo on 2024-09-13 05:45:45.413671833 +0000 UTC m=+787208.050641082.

Cheméo (<https://www.cheméo.com>) is the biggest free database of chemical and physical data for the process industry.